

Pacific Northwest Gigapop Meeting
October 23, 2018

Large Synoptic Survey Telescope (LSST) Scaling Issues and Network Needs

Heidi Morgan, Ph.D.
University of Southern California



Outline

- What is LSST?
- Data Management Facilities
- Network Requirements
- Deployment Calendar
- First Optic Light Demonstration 2017
- Demonstration SC18



Telescope Construction August 2018

Large Synoptic Survey Telescope



- This telescope will produce the largest evolving image of the Universe:
 - Expecting 10 million alerts, 15-30 Terabytes of data... every night!
 - First motion picture of our universe
 - This 10 year survey of the sky will catalog 37 billion objects (20B galaxies, 17B stars)
 - Each image is the size of 40 full moons
 - 3200 megapixels camera with 2-second readout
 - 8.4-m mirror, the width of a single tennis court



Webcam: Cerro Pachón Summit 2015-2017 (<https://gallery.lsst.org/bp/#/>)

Large Synoptic Survey Telescope(2)



WIDE:

- World's Widest Digital Camera

[Site \(<http://www.lsst.org/lsst/gallery/site>\)](http://www.lsst.org/lsst/gallery/site)




FAST:

- Rapidly scan the sky
- Charting - exploding supernovae to potentially hazardous near-Earth asteroids

[Mirror Casting \(<http://www.lsst.org/lsst/gallery/mirror-casting>\)](http://www.lsst.org/lsst/gallery/mirror-casting)



[Telescope \(<http://www.lsst.org/lsst/gallery/telescope>\)](http://www.lsst.org/lsst/gallery/telescope)



DEEP:

- Trace billions of remote galaxies
- Probes of the mysterious dark matter and dark energy

[Data \(<http://www.lsst.org/lsst/gallery/data>\)](http://www.lsst.org/lsst/gallery/data)



[LSST AmLight Trailer \(<https://youtu.be/T6eRshTuU88>\)](https://youtu.be/T6eRshTuU88)

[LSST & AmLight Video \(<https://youtu.be/c16h1yyS-78>\)](https://youtu.be/c16h1yyS-78)

[Seeing the Beginning of Time \(<https://tinyurl.com/ybk27qm7>\)](https://tinyurl.com/ybk27qm7)

LSST Data Management Facilities



LSST Operations: Sites & Data Flows

HQ Site

Science Operations
Observatory Management
Education & Public Outreach

Base Site

Base Center
Long-term storage (copy 1)
Data Access Center
Data Access & User Services

French Site


Satellite Processing Center
Data Release Production
Long-term Storage (copy 3)

LSST Data Facility

Processing Center
Alert Production
Data Release Production
Calibration Products Production
EPO Infrastructure
Long-term Storage (copy 2)
Data Access Center
Data Access and User Services

Summit Site

Telescope & Camera
Data Acquisition
Crosstalk Correction



LSST Network Requirements

The LSST operation will consist of two main channels:

- Control Channel

- Remotely operated from Tucson, AZ.
- Requires low bandwidth, low latency, and high priority,
- Bandwidth needs are about 2 Mbps

- Data Channels

- Multiple data streams summing up 90 Gbps:
 - Each 12.7GB data set (6.4GB picture + 6.3GB metadata) must be transmitted to the U.S. in 5 seconds
 - Database synchronization, etc.

- The end-to-end path must provide high resilience, low delay, multiple paths, and an efficient control plane to act in all network status changes

LSST End-to-End Path (1)


- Some R&E networks can accommodate some of the LSST requirements:
 - Multiple paths with multiple 100G links (including AmLight-ExP)
 - Dynamic provisioning, bandwidth reservation
- But R&E networks are interconnected through Academic Exchange Points that have challenges:
 - Heterogeneous configurations and services
 - Almost no support for network programmability (SDN)

LSST End-to-End Path (2)

- High demand end-to-end applications like LSST require that all networks in the path support QoS and Programmability
 - Including the Academic Exchange Points
 - Software Defined Exchanges (SDX) within the exchange point are a possible solution
 - AtlanticWave SDX is aiming to overcome those limitations that exchange points have
 - LSST is a primary use case for Awave-SDX, a collaboration between FIU, Gatech, and SouthernLight in Sao Paulo to be extended to AndesLight in Santiago, Chile this October

LSST End-to-End Path (3)

AtlanticWave-SDX



- Updated: now with four locations to cover: *La Serena*, Sao Paulo, Miami, and Atlanta.
- Thousands of KM of fiber between each location
- Split controller design
 - Central controller for interacting with users
 - Local controllers at each location


LSST Deployment Calendar

- From 2017 to 2020, the LSST network will be installed and fine-tuned (mainly for evaluations and simulations)
- Engineering "first light" anticipated in 2019
- Science "first light" in 2021
- Full operations for a ten-year survey commences in Q4 2022
- The LSST Network Engineering Team must guarantee all network requirements by 2021
 - Bandwidth guaranteed and resilience
 - Effective and efficient operation

Fiscal 2017				Fiscal 2018				Fiscal 2019				Fiscal 2020				Fiscal 2021				Fiscal 2022				Fiscal 2023				Fiscal 2024			
Calendar 2017				Calendar 2018				Calendar 2019				Calendar 2020				Calendar 2021				Calendar 2022				Calendar 2023				Calendar 2024			
Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
LSST Construction & Commissioning																				LSST Full Operations											
Net Deployment - Phase 1				Net Deployment - Phase 2																											
				LSST Early Operations																											

LSST Network Topology

- AmLight-Express (spectrum) is the primary
- MONET cable system is Ready For Service (RFS) Fortaleza, Brazil to Boca Raton, Florida
- South Atlantic Cable System (SACS) is lunched and will be RFS by the end of 2018
- AmLight-Protect 100G ring is the backup



SLA requirements for networking

■ General SLA:

- Mean Time Between Failures (MTBF) - **180 days**
- Mean time To Repair (MTTR) - **48 Hours**
- Different QoS profiles for different network conditions (chart below)

■ Bandwidth Required:


- Summit (Cerro Pachon) to Base(La Serena, Chile): 200Gbps
- Base (La Serena, Chile) to Archive (NSCA Champagne, Illinois, USA): 200Gbps
- Archive to Data Archive Centers - DACs (ex. DAC Lyon, France): 10Gbps

Traffic Types	Chile to Miami		Miami to Illinois	
	Full Connectivity	Minimal Connectivity	Full Connectivity	Minimal Connectivity
	Bandwidth Available 300G	Bandwidth Available 100G	Bandwidth Available 200G	Bandwidth Available 100G
Science & Data Backbone Transport	90	70	90	70
Other Behavior Aggregates	45	10	45	10
Chilean Academic Usage	Best Effort	Best Effort	Best Effort	Best Effort

Bandwidth Reservation for LSST	45%	80%	68%	80%
--------------------------------	-----	-----	-----	-----

First Optic Light Demonstration Dec 2017


- The LSST Network Engineering Team (NET) completed the first successful transfer of digital data over LSST/AURA fiber optic networks from the Summit Site on Cerro Pachon, Chile to the Base Site in La Serena, Chile and on to the Archive Site at NCSA in Champaign.
- A set of 6 x 10 Gbps Data Transfer Nodes (DTN)
- Sustained data rate of approximately 44 gigabits per second over a period of 24 hours




Demonstration Supercomputing Conference SC18

Petabyte data transfers between AURA in La Serena and NCSA in Illinois

@NCSA's Booth #3635




- *Turbo* version of the First Optic Light demo:
 - Instead of memory-to-memory tests, we will run 100G disk-to-disk tests
 - 100G FIONA DTNs installed in La Serena and NCSA
 - DTNs will be added to PRP's Maddash after SC18
 - Real files from (GEMINI or DECam) project will be used



Network Monitoring/Performance


- The *LSST Management Plan* defined a centralized Network Management System (NMS) for easy monitoring
 - To be used by LSST NOC and LSST Engineering teams
 - A single NMS will see all links, devices, CPUs, power supplies, etc. of all networks in the path
- perfSonar instrumenting the path: currently each site has two 10G ports dedicated for monitoring and performance evaluation; 100G nodes are planned for the future.
- End-to-end Performance Metrics: Latency, Packet Loss, Jitter, Maximum Payload Throughput
- Other performance and monitoring instruments being evaluated, such as the IRNC AMIS nodes (UMass)



Performance Instruments at AmLight

In-band Network Telemetry

- INT is an implementation to record operational information in the packet while the packet traverses a path between two points in the network:
 - Complements current out-of-band OAM mechanisms based on ICMP or other types of probe packets.
 - Basically, INT adds metadata to each packet with information that could be used later for troubleshooting activities.
- Example of information added:
 - Timestamp, ingress port, egress port, pipeline used, queue buffer utilization, WiFi link power, CPU utilization, Battery Utilization, Sequence #, and many others
- As metadata is exported directly from the Data Plane, Control Plane is not affected:
 - Translating: *you can track/monitor/evaluate EVERY single packet at line rate.*




Telemetry at AmLight: LSST

- What if the LSST doesn't manage to send its data in its 5-seconds transfer window?
 - For instance, because of packet loss, lack of capacity, lack of buffers, microburst, DoS attacks?
- If the data transfer window is missed, will AmLight engineering team be able to fix whatever it is happening before the next window (in 22 seconds)?
- How many windows are we going to miss if we have to troubleshoot it manually?
 - Don't forget our engineers will be sleeping!
 - ***AmLight-INT Project might be the solution!***

Telemetry at AmLight: A Use Case

- NSF IRNC: Backbone: AmLight In-band Network Telemetry (AmLight-INT), Award# OAC-1848746
- Focuses on LSST and Big Data needs
- AmLight-INT Project Plan:
 - Deploy P4/INT-capable switches
 - Deploy INT sinks (100G hosts) to collect metadata
 - Develop a new methodology to collect and export INT data in real time to feed SDN controllers and users with monitoring information
 - Create a Network Telemetry Design Pattern to be used by other R&E networks



New submarine cables in the South Atlantic

- **Monet:** Boca Raton, FL-Fortaleza, BR. Operational
- **South Atlantic Cable System (SACS):** Fortaleza, BR- Sangano, Angola. Q3 2018
- **South Atlantic Inter Link (SAIL):** Fortaleza, BR - Kribi, Cameroon. Q3 2018 (TBD)
- **EllaLink:** Fortaleza, BR - Sines, Portugal. RFS 2020
- **America Movil (AMX-1):** Fortaleza, BR - Jacksonville and Hollywood, FL. Operational
- **SABR:** Cape Town, SA - Recife, BR. RFS 2019
- Fortaleza is a landing point for all cables, except for SABR





AARCLight: Americas Africa Research and eduCation Lightpaths, NSF Award #OAC-1638990

- Planning activity that aims to
 - Define a strategy for research and education network connectivity between the US and West Africa along the South Atlantic
 - Coordinate planning efforts among stakeholders in the U.S., Africa, and Brazil
 - Create economies of scale
 - Understand the potential impact
 - From the use of the offered spectrum
 - Towards serving the broadest communities of interest in research and education


MeerKAT Radio Telescope

- MeerKAT is a 64-dish system
- MeerKAT will be integrated into the mid-frequency component of SKA
- Generates data at a rate of 4.7Gbps
- Data is transported either by tapes, or scientists travel to South Africa
- Data is collected and digitized at each antenna and then streamed via optical link to the Karoo Array Processor Building (KAPB) for science processing
- Clock signal is distributed from a central point to remote dishes
- Western Cape has many international collaborations with LSST, Very Large Array (VLA), and Arecibo observatory. South Africa LSST Committee members are Markus Bottcher (NWU), Fernando Camilo (SKA SA; Chair), Roger Deane (RU), Russ Taylor (UCT, UWC), Patricia Whitelock (SAAO, UCT), and Ted Williams (SAAO).



SKA Data Transport Requirements

- SKA will be the world's largest radio telescope
- Australia and South Africa are the host countries
- SKA Regional Science and Engineering Centers (SRC) will provide access to
 - SKA data products
 - Computational resources for processing and analysis
 - A long-term archive for SKA science data products
- NRENs will be critical to support data movement to SRCs and users



Adapted from
Richard Hughes-Jones

Challenges & Ongoing Efforts

- “LSST NOC” is a virtual NOC composed of multiple NOC teams
- Bi-annual AmLight-ExP South American Astronomy Coordination Committee (SAACC) meetings focus on networking needs for science & technology
- Monthly LSST Network Engineering Team (NET) calls and NET meetings at the SAACC
- Bandwidth Calendaring: Different network utilization profiles for night and day are being discussed
- Security and Applications are being handled by separate Association of Universities for Research in Astronomy (AURA) Data Management Teams



THANK YOU!

Heidi Morgan, Ph.D.
hlmorgan@isi.edu

Infrastructure, science application support, education, outreach and community building efforts are made possible by funding and or support from:

- National Science Foundation (NSF) awards: LSST #ACI-1202910, AmLight ExP #ACI-1451018, AtlanticWave SDX #ACI-1451024
- FAPESP, ANSP - grant no. 2008/52885-8
- Rede Nacional de Ensino e Pesquisa (RNP)
- REUNA
- CLARA
- Association of Universities for Research in Astronomy (AURA)
- Florida International University
- Internet2 and GRNOC
- ESnet
- Florida LambdaRail (FLR)
- National Center for Supercomputing Applications (NCSA)
- Latin American Research and Education community
- The many national and international collaborators who support our efforts

